

# Singlemode pigtail CONNECTICO

CO-X-000-XXX-XX-0,9-X-XX

Pigtail is a section of optical fiber with a connector on one side, it is the end of the fiber optic track, it is connected to the line by thermal or mechanical splice.



Pigtail CONNECTICO SMF SC/APC

## features:

- pigtail SMF CONNECTICO,
- 0,9 mm tube diameter

## standards and certificates:

- IEC 61753-1
- IEC 61300-3-34
- IEC 61300-3-6
- ITU-T G.652D
- RoHS

## technical specifications:

pigtail CONNECTICO SMF	APC	PC
insertion loss [dB]	< 0,25	< 0,25
return loss [dB]	> 65	> 45
durability	1000 cycles	1000 cycles
tensile strength [N]	100	100
cable diameter [mm]	0,9	0,9
length [m]	≥ 1	≥ 1
fiber type acc. ITU-T	SMF, G.652D or G.657A2	SMF, G.652D or G.657A2
operating temperature [ °C]	- 40 to +85	- 40 to +85
LSOH	yes	yes
tube colour	yellow	yellow
design	zirconia ceramic ferrule	zirconia ceramic ferrule

## sectors:



OPERATORZY  
TELEKOMUNIKACJI  
I MOBILNI



OPERATORZY  
TRANSMISJI  
DANYCH



OPERATORZY ISP I  
CATV



ENERGETYKA



PROJEKTANCI I  
WYKONAWCY



DEWELOPERZY



UCZELNIE



PRODUCENCI  
SYSTEMÓW I  
INTEGRATORZY



SŁUŻBY  
MUNDUROWE



PRZEDSIĘBIORSTWA  
UŻYTECZNOŚCI  
PUBLICZNEJ



KOLEJ

# Singlemode pigtail CONNECTICO

CO-X-000-XXX-XX-0,9-X-XX

## configuration :

code						description
CO-S-000-						pigtail CONNECTICO
	SCA-					SC/APC connector
	SCP-					SC/PC connector
	LCA-					LC/APC connector
	LCP-					LC/PC connector
	E2A-					E2000/APC connector
	E2P-					E2000/PC connector
	FCA-					FC/APC connector
	FCP-					FC/PC connector
	STP-					ST connector
		2D-				SMF G.652D
		7A2-				SMF G.657A2
			0,9-			cable diameter 0,9 [mm]
			2,0-			cable diameter 2 [mm]
				X-		length [m]
					YE	colour yellow
					WH	colour white

## example :

CO-S-000-SCA-2D-0,9-2-YE

pigtail SM SC/APC, G.652D, LSOH, 0,9mm, length 2m, yellow