

Multimode patchcord CONNECTICO

CO-X-XXX-XXX-OMx-2,0-X-X

Optical patchcord it is fibre optic section terminated on both side with connectors. Is an extension of the fiber optic path. Used to patch between fiber ports.



Patchcord duplex CONNECTICO SC/PC – LC/PC OM2

features:

- patchcord MMF CONNECTICO,
- 2mm cable diameter

standards and certificates:

- IEC 61753-1
- IEC 61300-3-34
- IEC 61300-3-6
- ITU-T G.652D
- RoHS.

technical specifications:

Patchcord CONNECTICO 2 MM class	PC		
insertion loss IL[dB]	< 0,3		
return loss [dB]	> 35		
durability	1000 mating cycles		
tensile strength [N]	100		
cable diameter[mm]	2,0		
length [m]	0,5 – 100		
type of fiber	50/125 MMF OM2	50/125 MMF OM3	50/125 MMF OM4
operating temperature [°C]	- 40 to +85		
LSOH	yes		
cable colour	orange	turquoise	violet
design	zirconia ceramic ferrule		

sectors:



Multimode patchcord CONNECTICO

CO-X-XXX-XXX-OMx-2,0-X-X

configuration:

code								description
CO2-								patchcord CONNECTICO
	S-							patchcord simplex
	D-							patchcord duplex
		SCP-						SC/PC connector
		E2P-						E2000/PC connector
		LCP-						LC/PC connector
		FCP-						FC/PC connector
		STP-						ST/PC connector
			SCP-					SC/PC connector
			E2P-					E2000/PC connector
			LCP-					LC/PC connector
			FCP-					FC/PC connector
			STP-					ST/PC connector
				OM2-				50/125 OM2 MMF
				OM3-				50/125 OM3 MMF
				OM4-				50/125 OM4 MMF
					2,0-			cable diameter 2 [mm]
						X-		length [m]
							OG	colour orange (OM2)
							TQ	colour turquoise (OM3)
							VT	colour violet (OM4)

example:

CO2-D-SCP-SCP-OM2-2,0-2-OG patchcord MM duplex SC/PC-SC/PC, OM2, LSOH, 2,0mm, 2m, orange