


CTB2-X-X-000-SCA-L1-7B3-xx-xx-xx

Socket CTB2-A are designed as a termination point of subscriber's fiber optic line



Subscriber socket CTB2-A



Subscriber socket CTB2-A



Subscriber socket CTB2-A
/highlighted locking catch/

main features:

- wall mounted FTTH outlet,
- possibility of mounting on flush-mounted box ensures high aesthetics of implementation of indoor installations,
- cover of socket closed by click,
- possibility of terminating up to 2 subscriber cables,
- location of the adapter (optionally two) from the bottom of the socket provides protection against laser radiation,
- possibility of entrancing the cable through one of the 4 holes, including the back side of the socket
- selected part of socket space for collecting a pigtail supply,
- socket design ensures secure fiber arrangement,
- includes tippable cover,
- splice tray with a clip protecting against opening.

kit includes::

- SC/APC adapter with protection shutter,
- assembly screws kit,
- cable ties.

optional accessories:

- heat shrink sleeves,
- SC/APC adapter with protection shutter,
- G.657 pigtail with SC/APC connector,,
- available version without removable tray.

sectors:



TELECOMMUNICATION
AND MOBILE
OPERATORS



DATA
TRANSMISSION
OPERATORS



ENERGETICS



DESIGN AND
EXECUTION
COMPANIES



DEVELOPERS

CTB2-X-X-000-SCA-L1-7B3-xx-xx-xx

technical parameters:

CTB2-X-X-000-SCA-L1-7B3-xx-xx-xx	
dimensions (width x height x depth) [mm]	80 x 100 x 24
max. number of cable entry	4
max. number of commutation fields	2
max. number of thermal or mechanical splices	2
material	ABS, color RAL 9016
weight [g]	73

ordering:

0	1	2	3	4	5	description
CTB2-						fiber optics subscriber socketCTB2
	A-					adapter SC/APC – 1 pc.
	A2-					adapter SC/APC – 2 pc.
		S-000-SCA-L1-7B3-				pigtail 1J SC/APC on G.657B3 cable
		D-000-SCA-L1-7B3				pigtail 2J SC/APC on G.657B3 cable
			3,0			cable diameter [mm]
			2,8			cable diameter [mm]
				x-		pigtail length [m]
					IV	ivory
					BK	black
					WH	white
					BN	brown
					GY	grey

example:

CTB2-2A-D-000-SCA-L1-7B3-3,0-15-WH – subscriber ending- CTB2 socket, adapter SC/APC with cover, pigtail 2J SC/APC, SM, Lite, G.657B3, LSOH, 3,0mm, 15m, white